

# AQUAGARD™ M Non-Slip Topcoat

Two-Part UV Resistant Protective Coating

---

## Product Description

A tough, fast curing, non-slip, aliphatic polyurethane coating designed for protection of AQUAGARD™ M membrane systems in all exposed situations. AQUAGARD™ M Non-Slip Topcoat is UV resistant - it provides a durable, service foot-trafficable finish to roof and deck areas.

## Uses

AQUAGARD™ M Non-Slip Topcoat is used for colour-fast, non-slip exposed areas on plant room and lift motor room roofs, balconies, decks, perimeter turn-ups, penetrations and sill or window flashings.

It may be used to give colour fast protection to all grades of AQUAGARD™ M waterproof membranes used in exposed external situations.

## Features

- Simple application, easy to use and fast cure
- UV Resistant and foot trafficable
- Fire Resistant
- Fast Cure - Quick access for trades
- Permanently flexible - total adhesion
- Immediate Resistance to rain damage

AQUAGARD™ M Non-Slip Topcoat may be painted or tiled as required, after first sealing with EPOCOTE™ F100W Grey.

## Preparation

Surface of AQUAGARD™ M membrane must be clean and dry.

## Application

Mix each component separately with a clean stirrer blade, then combine together in a clean dry container and mix thoroughly with high speed dissolver for 5 minutes prior to application. Mix ratio Resin : Hardener is 5:1 by weight.

Apply in two coats by brush or roller – apply second coat in cross direction to the first to give a uniform finish.

For spraying use a single wet-on-wet spray application.

Do not use mixed product once it has become thick and stringy, it should be discarded.

Do NOT add solvent.

## Typical Properties

|                           |            |
|---------------------------|------------|
| Drying Time @ 25°C        | 2 hours    |
| Shore Hardness            | 75-80 °A   |
| Tensile Strength (AS1145) | 2 MPa      |
| UV Resistance (System)    | Excellent  |
| Fire Resistance           | UL Class A |

## Coverage

AQUAGARD™ M Non-Slip Topcoat A/B mixed – minimum 0.3kg/m<sup>2</sup> for minimum 0.15mm Dry Film Thickness (DFT).

## Supply and Packaging

AQUAGARD™ M Non-Slip Topcoat Resin Grey – 15 kg pails

AQUAGARD™ M Non-Slip Topcoat Hardener – 3 kg pails

## Shelf Life

Do not store product exposed to weather and sun. When kept in a cool, dry, protected area, sealed pails have a 12-month shelf life, but once opened may solidify within a few days.

## Clean-up

Use MULTITEK™ Xylene or methylated spirits before curing. Exercise care when using solvent, review all Material Safety Data Sheet (MSDS) before use.

## Health and Safety

In case of spills and accidents, refer to the MSDS of the products or when in doubt contact your local GCP representative.

Always wear protective clothing, gloves and protective goggles when handling chemical products.

For full information, consult the relevant MSDS.

## Limitations

Information contained in this document does not cover all possible application scenarios or imply product suitability for an application. Please contact your local GCP representative or the GCP Technical Department for further information.

## Warranties

GCP and contractors recognised by GCP as experienced in the application of GCP products will provide warranties for individual projects. Warranty periods offered are dependent on project details and complexity. Requests for very long warranty periods may necessitate increased membrane thicknesses to ensure longevity.

Contact your local GCP representative for further details.

Release Date: 02/11/18. The information contained in this product data sheet supersedes all previous versions.

[gcpat.com.au](http://gcpat.com.au) | For technical information: [anz.enq@gcpat.com](mailto:anz.enq@gcpat.com)

Australia 1800 334 444 New Zealand 0800 552 235 China Mainland +86 21 3158 2888 Hong Kong +852 2675 7898 India +91 124 402 8972 Indonesia +62 21 893 4260 Japan +81 3 5226 0231 Korea +82 32 820 0800 Malaysia +60 3 9074 6133  
Philippines +63 49 549 7373 Singapore +65 6265 3033 Thailand +66 2 709 4470 Vietnam +84 8 3710 6168

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

AQUAGARD™, EPOCOTE™ and SILCOR® are trademarks of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies, Inc. All rights reserved.

Printed in Australia

GCP PDS 029 07/17

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Australia Pty. Ltd., 14 Colebard Street West, Archerfield, Brisbane, Queensland 4108, Australia

This document is only current as of the last updated date stated below and is valid only for use in Australia. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on [www.gcpat.com.au](http://www.gcpat.com.au). Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2022-01-31

[gcpat.com.au/solutions/products/aquagard-m-non-slip-topcoat](http://gcpat.com.au/solutions/products/aquagard-m-non-slip-topcoat)